

MACHUELOS EN ACERO ALTA VELOCIDAD

PARA TUBERIA NPS



ROSCA CILINDRICA AMERICANA ASA B 2.1 - 1960

STRAIGHT TPIPE TAPS
HIGH SPEED STEEL - GROUND THREAD

Codigo	Tamaño	Diam. Nominal en milésimos de pulgada	Longitud total mm	Longitud rosca mm	Diam Vástago mm.	Tamaño Cuadro mm
0066	1/16-27	7.70	54.00	17.50	7.93	9.50
0067	1/8-27	10.10	54.00	19.10	11.11	8.33
0068	1/4-18	13.40	61.90	27.00	14.29	10.69
0069	3/8-18	16.80	65.90	27.00	17.78	13.49
0070	1/2-14	21.00	79.40	34.90	17.46	13.08
0071	3/4-14	26.30	82.60	34.90	23.02	17.25
0072	1- 11 1/2	32.90	95.30	44.50	28.58	21.41

MACHUELOS EN ACERO ALTA VELOCIDAD

PARA POLEAS ROSCA AMERICANA



ROSCA AMERICANA 60°

TOLERANCIA DE AJUSTE H3*
PULLEY TAPS
HIGH SPEED STEEL - GROUND THREAD

Codigo	Diametro Nominal	Equivalencia en mm.	Longitud total en pulgadas	Longitud rosca en pulgadas	Diam vástago en pulgadas	Tamaño cuadro en pulgadas
0201	1/4-20 NC	6.35	6	1	.	0.191
0208	1/4-20 NC	6.35	8	1	0.255	0.191
0202	5/16-18 NC	7.94	6	1 1/8	0.318	0.238
0209	5/16-18 NC	7.94	8	1.125	0.318	0.238
0214	5/16-18 NC	7.94	10	1.125	0.318	0.238
0203	3/8-16 NC	9.53	6	1.25	0.381	0.286
0210	3/8-16 NC	9.53	8	1.25	0.381	0.286
0215	3/8-16 NC	9.53	10	1.25	0.381	0.286
0220	3/8-16 NC	9.53	12	1.25	0.381	0.286
0204	7/16-14 NC	11.11	6	1.4375	0.444	0.333
0211	7/16-14 NC	11.11	8	1.4375	0.444	0.333
0216	7/16-14 NC	11.11	10	1.4375	0.444	0.333
0205	1/2-13 NC	12.7	6	1.6562	0.507	0.38
0212	1/2-13 NC	12.7	8	1.6562	0.507	0.38
0217	1/2-13 NC	12.7	10	1.6562	0.507	0.38
0221	1/2-13 NC	12.7	12	1.6562	0.507	0.38
0206	5/8-1 1 NC	15.88	6	1.8125	0.633	0.475
0213	5/8-1 1 NC	16.88	8	1.8125	0.633	0.475
0218	5/8-1 1 NC	17.88	10	1.8125	0.633	0.475
0222	5/8-1 1 NC	18.88	12	1.8125	0.633	0.475
0207	3/4-10 NC	19.05	6	2	0.759	0.569
0219	3/4-10 NC	21.05	10	2	0.759	0.569
0223	3/4-10 NC	22.05	12	2	0.759	0.569